



Pallet Specifications

For reference, the following are the acceptable pallet dimensions & specifications. In addition you should ensure that the freight is correctly wrapped & safely banded/attached to the pallet before accepting responsibility for its safe transshipment.




“A” PALLET

1.2m x 1.2m x 1m high 500kgs Max



“B” PALLET

1.6m x 1.2m x 2.2m high 1000kgs Max



“C” PALLET

2.6m x 1.2m x 2.2m high 1250kgs Max

IF IN DOUBT – ASK!

Bagged Pallet Specification

It is imperative that the Fortec Pallet Network only carries the highest quality freight. Of all types of palletised freight, bagged traffic remains the most at risk in terms of damage.

In order to minimise the risks the following specifications must be adhered to when inputting bagged traffic through the network.

1. Cardboard layer between the bottom layer of bags & the pallet to prevent bags sagging and fork damage
2. Cardboard layers every approx 60 cms
3. Cardboard lid on top of pallet
4. A minimum height of 40cms strong cardboard surround from top of pallet
5. No overhanging of pallet
6. Complete & tight shrink wrap
7. Do not stack/Palletcap on top of pallet
8. Bags should be brick stacked in layers for stability

We will not accept responsibility or entertain claims for damage to bagged pallets presented outside the above specification

